


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00316	Connector, dc plug, 4.75x1.7xL21 mm, brass, nickel plated, molding type, white insulators	1	
2	30-00405	Wire, 2C TS, 24 AWG, UL2468, 300V, 80C, 3.0 mm, VW-1, PVC, 87A, white	1	
3	24-00001	Overmold, PVC, white	1	



Notes:
Cables individually tied and bundled in groups of 10
Functionally equivalent components may be substituted
4.5 A, 48 Vdc

Wiring Diagram	
50-00316	wire color
center	white with stripe
sleeve	white

Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com	
A	12/21/2015	Initial release	Verified:			
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description:	Size:	Part number:
				Cable, 1830 mm, 4.75x1.7x9.5 mm 50-00316 dc plug to stripped tinned, 24 AWG, 30-00405 wire, white	A	10-01257
					Scale: 1:2	  Sheet 1 of 1

5 4 3 2 1