Ratings
Voltage: 300 V
Temperature
Static: -40 to 105 °C
Dynamic: -20 to 105 °C
Flammability: VW-1
Water resistant: 75 °C
Oil resistant: 60 °C (jacket)
≥50% elongation and tensile strength after aging
UV resistance: jacket, 720 hours xenon or carbon arc exposure
≥80% tensile strength and elongation after aging

Conductor
Conductor count: 4
Gauge: 24 AWG 0.21 mm²
Material: tinned copper strands
Strand size: Ø 0.08 mm x 41
Resistance at 20 °C: 94.2 Ω /km Max

Insulator
Material: PVC
Color: brown, white, blue, black
Diameter: ∅1.4 ±0.10 mm
Nominal thickness: 0.38 mm
Resistance at 20 °C: 10 MΩ /km Min

Wrap
Material: Cotton paper

Outer jacket
Material: PVC, 80A
Color: Black
Diameter: ∅5.1 ±0.20 mm
Nominal thickness: 0.80 mm

Wire marking: E339579 UL AWM STYLE 20387 24 AWG 105°C 300V VW-1 60°C OIL RESISTANT UV RESISTANT TENSILITY

Use: External wiring





Revision:	Date:	Description:
A	2/27/2023	Initial release

Prepared: MP Digitally signed by MP Date: 2023.02.28 07:42:18 -08'00'

Verified: PB Digitally signed by PB Date: 2023.02.28 14:59:20 -08'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:

RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:

Wire, 4C TS, 24 AWG, UL20387, 300V, 105C, 60C oil, UV, 5.1 mm, VW-1, PVC, 80A, black

TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A

Part number: 30-02979

Scale: 10:1

Sheet 1 of 1

To see a custom version of this cable assembly, call Tensility at 541-323-3228 or email engineering@tensility.com

5 4 3 2 1